



SERVICE PARTS LIST

BULLETIN NO.
55-40-5301

SPECIFY CATALOG NO. AND SERIAL NO. WHEN ORDERING PARTS		REVISED BULLETIN	DATE
120mm DEEP CUT BANDSAW		55-40-5300	Nov. 2011
CATALOG NO. 6232-55	STARTING SERIAL NO. 678B	WIRING INSTRUCTION 58-03-0750	

EXAMPLE:

00	0
----	---

 Component Parts (Small #) Are Included
 When Ordering The Assembly (Large #).

FIG.	PART NO.	DESCRIPTION OF PART	NO.	REQ.	FIG.	PART NO.	DESCRIPTION OF PART	NO.	REQ.
1	22-64-4610	Cord Set Assembly	(1)		60	42-12-0070	Blade Pulley Axle	(2)	
2	44-76-0210	Cord Protector	(1)		61	06-82-8864	10-24 x 1/2" Pan Hd. Sem T-25	(2)	
3	31-17-0155	Cord Clamp	(1)		★ 62	42-38-0040	Bumper	(1)	
4	06-82-7270	8-16 x 5/8" Slt. Plastite T-20	(2)		63	06-82-5330	10-32 x 5/8" Pan Hd. Tapt. T-25	(2)	
5	06-82-5292	1/4-20 x 7/8" Pan Hd. Taptite T-30	(4)		64	42-28-0205	Front Blade Guide Block	(1)	
6	31-44-0725	Right Handle Half	(1)		65	42-28-0210	Rear Blade Guide Block	(1)	
7	06-82-7270	8-16 x 7/8" Slt. Plastite T-20	(4)		66	02-25-0260	Cam Follower	(6)	
8	31-44-0720	Left Handle Half	(1)		67	06-82-5574	10-24 x 7/8" Pan Hd. Tapt. T-25	(2)	
9	-----	Suppressor	(1)		68	06-82-8864	10-24 x 1/2" Pan Hd. Sem T-25	(1)	
10	23-66-0775	Switch / Suppressor Kit	(1)		69	43-54-0250	Blade Guard	(1)	
11	06-82-7252	8-32 x 3/8" Pan Hd. Slt. Tapt. T-20	(1)		70	06-82-9264	10-24 x 1/2" Pan Hd. Tapt. Shld. T-25	(1)	
★ 12	28-62-0032	Blade Release Lever	(1)		71	-----	Bandsaw Blade - Select From Catalog	(1)	
14	45-88-7105	Wave Washer	(1)		72	02-50-3235	Needle Bearing	(1)	
15	06-82-3024	1/4-20 x 1/2" Fil. Hd. Taptite T-30	(3)		★ 73	45-08-0172	Blade Release Shaft	(1)	
16	06-75-4675	3/8-16 x 1" Skt. Hd. Screw	(1)		74	45-36-0720	Retaining Plate Spacer	(4)	
17	31-44-0330	Front Handle	(1)		75	44-52-0120	Blade Backing Pad	(1)	
18	23-44-0220	Brush Cap	(2)		76	28-41-0920	Front Pulley Guard	(1)	
19	22-18-0671	Carbon Brush Assembly	(2)		77	42-40-1010	Bronze Bushing	(1)	
20	22-22-1355	Brush Holder Assembly	(2)		78	44-66-0550	Pulley Guard Retaining Plate	(2)	
21	06-82-5294	1/4-20 x 3/4" Pan Hd. Taptite T-30	(6)		79	06-82-3810	1/4-20 x 1-1/4" Flat Hd. Taptite T-27	(4)	
22	28-90-0200	Pulley Support	(1)		80	40-50-0710	Blade Tension Spring	(2)	
23	28-50-6382	Motor Housing	(1)		★ 81	06-75-1991	.25-20 Hex Bolt Cap Screw	(2)	
24	02-04-0913	Ball Bearing	(1)		82	06-57-5000	1/4-20 Lock Nut	(2)	
25	31-55-0145	Coil Shield	(1)		83	42-18-0190	Blade Tension Bar	(2)	
26	23-16-0420	Field Insulator	(1)		84	06-82-5298	1/4-20 x 1" Pan Hd. Taptite T-30	(2)	
27	18-50-0101	Field	(1)		85	22-84-0770	Fan	(1)	
28	06-82-7410	8-16 x 1-7/8" Pan Hd. Plastite T-20	(2)						
29	31-05-0170	Fan Baffle	(1)						
30	16-50-1101	Armature	(1)						
31	02-04-1050	Ball Bearing	(1)						
32	06-65-1155	3/16 x 5/8" Groove Pin	(1)						
33	28-28-1699	Diaphragm	(1)						
34	02-04-1020	Ball Bearing	(1)						
35	32-40-1680	Intermediate Gear	(1)						
36	06-42-1200	Woodruff Key	(1)						
37	36-18-0050	Worm Shaft	(1)						
38	02-04-1030	Ball Bearing	(1)						
39	28-14-2110	Gear Case	(1)						
40	06-82-3060	1/4-20 x 1-5/16" Pan Hd. Taptite T-30	(4)						
41	06-82-5270	Nameplate Screw	(2)						
42	12-99-0067	Nameplate Blank	(1)						
43	06-82-5394	5/16-18 x 13/16" Pan Hd. T-40	(2)						
44	02-04-1210	Ball Bearing	(1)						
45	32-90-0110	Worm Gear	(1)						
46	23-16-1340	Insulator	(1)						
47	36-66-0525	Worm Gear Shaft	(1)						
48	02-04-2700	Ball Bearing	(1)						
49	14-46-1175	Chain/Sprocket Kit	(1)						
50	06-82-8842	8-32 x 3/8" Pan Hd. Tapt. Sem T-20	(2)						
51	-----	Roller Chain	(1)						
52	45-69-0010	Blade Pulley Tire	(2)						
53	45-88-7165	Pulley Hub Washer	(4)						
54	34-60-1400	Snap Ring	(2)						
55	25-20-1220	Blade Pulley Cover	(2)						
56	06-82-3060	1/4-20 x 1-5/16" Fil. Hd. Tapt. T-30	(3)						
57	28-95-0120	Blade Pulley	(2)						
58	42-40-0580	Sleeve Bearing	(4)						
59	-----	Sprocket	(1)						

FIG. NOTES
 34,35,
 36,37,38 Assemble and install in Gear Case before 44, 45, 47, 48.

43 Apply Type 242 Blue Loctite. Torque to 8.5 Nm - 13.0 Nm.

66 Torque to 2.3 - 3.4 Nm.

75 Apply Loctite Speed Bonder 326.

83 Dimension between outside edges of blade tension bars
 93.7mm ± 1.6mm.

FIG. LUBRICATION
 39 85 grams Type "G" Grease, No. 49-08-4140.
 42.5 grams in each of two locations. (See Illustration).

