



WARNING
SWITCH POLARITY SENSITIVE
 If wired incorrectly with connector block, switch **will be** damaged and destroyed!

NOTE: Proper polarity in connector block requires leads to be crossed, as illustrated.

WIRING SPECIFICATIONS

Wire No.	Wire Color	Origin or Part No.	Gauge	Length	Terminals, Connectors and End Wire Preparation
1	Green	*	20	2-1/4	* Component of the circuit board assembly.
2	Dark Blue	*	20	2-1/4	* Component of the circuit board assembly.
3	White/Blue	*	20	8-1/4	* Component of the circuit board assembly.
4	Red/White	*	20	6-1/2	* Component of the circuit board assembly.
5	Green/White	*	20	6-7/8	* Component of the circuit board assembly.
6	White	*	20	7-3/4	* Component of the circuit board assembly.
7	Purple	*	20	6-1/2	* Component of the circuit board assembly.
8	Light Blue	*	20	6-1/2	* Component of the circuit board assembly.
9	Yellow	*	20	4	* Component of the circuit board assembly.

BULK LEAD WIRE - BULLETIN 58-01-0003

NOTE:
 All lead lengths are before stripping.
 All leads must be held to ± .125" unless specified elsewhere.
 Strip wire per ES 13-11.
 Crimp terminals per ES 13-15.

TERMINAL DESCRIPTION		
Code	Part No.	Qty.